## **DK-PTS DESK INSTRUMENT**



The DK-PTS is a kit of parts to allow the 201PTS press-tospeak telephone to be used as a desk instrument.

It comprises a stainless steel mounting plate fitted with rubber feet, a flexible 3 metre CAT5 cable and an RJ45 surface mounting socket. The desk-kit is supplied pre-wired to the PTS instrument.

The installer should fit the RJ45 socket to a fixed position well within 3 metres of the intended phone position and connect the fixed wiring to the IDC terminals (using the disposable tool provided) as follows:

| Terminal | Code           | Flex colour |
|----------|----------------|-------------|
| 1        | Vid            | WHT/ORG     |
| 2        | 20+            | ORG/WHT     |
| 3        | L              | WHT/GRN     |
| 4        | Р              | BLU/WHT     |
| 5        | 1              | WHT/BLU     |
| 6        | B,F,G/20-/SCRN | GRN/WHT     |
| 7        | Α              | WHT/BRN     |
| 8        | Sig            | BRN/WHT     |

Please note: Because of the limited number of conductors in the flexible lead, terminal 6 is a combined common. These wires are separate in the main wiring but should be combined in the desk kit socket.

For additional details and settings for the 200PTS please refer to the main instruction sheet.

DK-PTS inst.pmd

The Entryphone Company Limited 23 Granville Road London SW18 5SD 020-8870 8635 entryphone.co.uk